(J
Γ	١
(J

LUMINAIRE ARM DATA							
M Projected Length	N Rise	Min OD at Pole	Nominal Thickness				
4.6 m (15')	1450 mm (51") ±	108 mm (4 ¹ / ₄ ")	3.04 mm (0.1196")				
61 m (201)	750 mm (30") +	127 mm (5")	4.55 mm (0.1793")				

	POLE DATA				
Pole Extension		Min OD		Min	
Туре	Height	Base	Тор	Thickness	
Type 5	I.5 m (5')	165 mm (61/2")	152 mm (6")	4.55 mm (0.1793")	
Type I0	3.0 m (10')	184 mm (7 ¹ / ₄ ")	I52 mm (6")	4.55 mm (0.1793")	





Drill and tap thru chord plate for 25 mm (I") ø HS cap screws Tot 4 holes equalit spaced.

UPPER CHORD PLATE

Truss axis



GENERAL NOTES:

SPECIFICATIONS

Design: AASHTO specifications for the design and construction of structural supports for highway signs, dated 1994.

LOADING

Wind Loadings: I29 km/h (80 mph) AASHTO

UNIT STRESSES

Structural Steel: fy = 331 MPa (48,000 psi) tapered steel tube (pole) fy = 248 MPa (36,000 psi) unless otherwise noted

Size, mm (inches)

NOTES:

- I. The Contractor shall verify all controlling field dimensions before ordering or fabricating any material.
- 2.All steel shall be galvanized after fabrication.
- 3.Bolt hole locations may vary at the discretion of the Engineer.


STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION


LIGHTING STANDARDS TYPE 5 AND TYPE 10 **OVERHEAD SIGN MOUNTED**


These "Standard Plans for Construction of Local Streets and Roads" contain units in two systems of measurement: international System of Units (SI or "metric") and United States Standard Measures shown in the parentheses (). The measurements expressed in the two systems are not necessarily equal or interchangeable. See the "Foreword" at the beginning of this publication.


NO SCALE











SECTION K-K

SHIM DETAIL